

Badotherm model BDT70 duplex series are available as 60 mm dia. These duplex gauges are used for gaseous and non-aggressive liquid media, applications include lubricating oil pressure measurement for diesel engines, air pressure measurement for tanks and break cylinders from trucks, busses, available with or without electric signal etc.



BDT70

duplex automotive pressure gauge

mounting variations

- type A bottom connection, direct mounting
- type B panel mounting, clamp fixing, back connection
- type C surface mounting, bottom connection
- type D back connection, direct mounting
- type E panel mounting, back connection
- type F panel mounting, bottom connection

technical specification model BDT70

diameter	connection	window	ranges
60 mm	M12 x 1.5	glass	0-10 bar
casing	tube	movement	dial
steel black painted	copper alloy	brass	aluminium
bezel	socket	pointer	accuracy
crimped	brass	aluminium	2.5% FSD

Note: protection class is IP40

gauge options and special executions at extra costs

casing	cadmium plated steel
bezel	black steel painted brass
window	plastic
dials	customized – i.e., non standard ranges or logos
certificates	calibration -; conformity -; material
manuals	installation and maintenance
connection size	NPT; METRIC; BSPT; acc JIS in various sizes
restrictor	brass
soldering	silver soldered for steam applications
light	with light sleeves in the casing