

Stafford

METRIC RIGID SHAFT COUPLINGS ONE-PIECE SPLIT CLAMP-TYPE WITH KEYWAYS

- Fully metric, including clamp screws
- Mate two shafts with zero backlash
- Keyways provide added torque capacity and fixed shaft phasing
- Smooth bore protects shafts from damage
- Superior torque capacity over set-screw-type couplings



Stafford Metric Rigid Shaft Couplings are fully metric in all specifications, including the clamping screws.

Designed for aligned shafts, the 1-Piece Clamp-Type Coupling makes two shafts function as one. Standard keyways provide added torque capacity and fixed shaft phasing. It is ideal for overhung or unsupported shafts and is an excellent way to attach items such as mixer paddles and shaft extensions.

Metric Clamp-Type Couplings are available in straight-through bores. They are precision machined, non-marring, easy to adjust, with high clamping power.

Stocked in:

- Steel
- Stainless Steel

1 2

<u>Part Number</u>	<u>Bore Size A</u>	<u>Bore Size B</u>	<u>Material</u>	<u>Type</u>	<u>Outside Diameter</u>	<u>Total Length</u>
5SM008008K	8 mm	8 mm	Stainless Steel	Low Profile	18 mm	30 mm
5LM008008K	8 mm	8 mm	Steel	Low Profile	18 mm	30 mm
5SM009009K	9 mm	9 mm	Stainless Steel	Low Profile	24 mm	35 mm
5LM009009K	9 mm	9 mm	Steel	Low Profile	24 mm	35 mm
5SM010010K	10 mm	10 mm	Stainless Steel	Low Profile	24 mm	35 mm
5LM010010K	10 mm	10 mm	Steel	Low Profile	24 mm	35 mm
5SM012012K	12 mm	12 mm	Stainless Steel	Low Profile	28 mm	45 mm
5LM012012K	12 mm	12 mm	Steel	Low Profile	28 mm	45 mm
5SM014014K	14 mm	14 mm	Stainless Steel	Low Profile	30 mm	50 mm

<u>Part Number</u>	<u>Bore Size A</u>	<u>Bore Size B</u>	<u>Material</u>	<u>Type</u>	<u>Outside Diameter</u>	<u>Total Length</u>
5LM014014K	14 mm	14 mm	Steel	Low Profile	30 mm	50 mm
5SM015015K	15 mm	15 mm	Stainless Steel	Low Profile	34 mm	50 mm
5LM015015K	15 mm	15 mm	Steel	Low Profile	34 mm	50 mm
5SM016016K	16 mm	16 mm	Stainless Steel	Low Profile	34 mm	50 mm
5LM016016K	16 mm	16 mm	Steel	Low Profile	34 mm	50 mm
5SM018018K	18 mm	18 mm	Stainless Steel	Low Profile	36 mm	60 mm
5LM018018K	18 mm	18 mm	Steel	Low Profile	36 mm	60 mm
5SM020020K	20 mm	20 mm	Stainless Steel	Low Profile	40 mm	65 mm
5LM020020K	20 mm	20 mm	Steel	Low Profile	40 mm	65 mm
5SM025025K	25 mm	25 mm	Stainless Steel	Low Profile	45 mm	65 mm
5LM025025K	25 mm	25 mm	Steel	Low Profile	45 mm	65 mm
5SM030030K	30 mm	30 mm	Stainless Steel	Low Profile	54 mm	75 mm
5LM030030K	30 mm	30 mm	Steel	Low Profile	54 mm	75 mm
5SM035035K	35 mm	35 mm	Stainless Steel	Low Profile	57 mm	80 mm
5LM035035K	35 mm	35 mm	Steel	Low Profile	57 mm	80 mm
5SM040040K	40 mm	40 mm	Stainless Steel	Low Profile	60 mm	90 mm



Stafford Manufacturing Corp.

256 Andover St.
Wilmington, MA 01887

Phone: 978.657.8000

Fax: 978.657.4731

For More Information:

800.695.5551

sales@staffordmfg.com